

Removing fasteners from rubber backing

Peel the rubber backing away from the photo-etched part, we don't recommend peeling the part from the rubber backing.

Use a tweezers to handle the parts. Oils from your fingers can cause nickel plated silver to tarnish over time.

Also, we recommend that you coat the fasteners with Tamiya Clear Coat after placement. Coating with clear will keep fasteners bright and shiny over time.

Method of Application

There are two ways you can attach our fastener heads:

1. CA glue or Super glue
2. Tamiya Clear Coat.

Make sure the surface where the fastener is to be glued is scraped clean of any paint or finish previously applied.

We don't recommend placing adhesive on the fastener first. Place a dab of whichever adhesive you choose on the part of the model where the fastener is to be positioned.

Removing fasteners from rubber backing

Peel the rubber backing away from the photo-etched part, we don't recommend peeling the part from the rubber backing.

Use a tweezers to handle the parts. Oils from your fingers can cause nickel plated silver to tarnish over time.

Also, we recommend that you coat the fasteners with Tamiya Clear Coat after placement. Coating with clear will keep fasteners bright and shiny over time.

Removing fasteners from rubber backing

Peel the rubber backing away from the photo-etched part, we don't recommend peeling the part from the rubber backing.

Use a tweezers to handle the parts. Oils from your fingers can cause nickel plated silver to tarnish over time.

Also, we recommend that you coat the fasteners with Tamiya Clear Coat after placement. Coating with clear will keep fasteners bright and shiny over time.

Method of Application

There are two ways you can attach our fastener heads:

1. CA glue or Super glue
2. Tamiya Clear Coat.

Make sure the surface where the fastener is to be glued is scraped clean of any paint or finish previously applied.

We don't recommend placing adhesive on the fastener first. Place a dab of whichever adhesive you choose on the part of the model where the fastener is to be positioned.

Removing fasteners from rubber backing

Peel the rubber backing away from the photo-etched part, we don't recommend peeling the part from the rubber backing.

Use a tweezers to handle the parts. Oils from your fingers can cause nickel plated silver to tarnish over time.

Also, we recommend that you coat the fasteners with Tamiya Clear Coat after placement. Coating with clear will keep fasteners bright and shiny over time.

Method of Application

There are two ways you can attach our fastener heads:

1. CA glue or Super glue
2. Tamiya Clear Coat.

Make sure the surface where the fastener is to be glued is scraped clean of any paint or finish previously applied.

We don't recommend placing adhesive on the fastener first. Place a dab of whichever adhesive you choose on the part of the model where the fastener is to be positioned.

Method of Application

There are two ways you can attach our fastener heads:

1. CA glue or Super glue
2. Tamiya Clear Coat.

Make sure the surface where the fastener is to be glued is scraped clean of any paint or finish previously applied.

We don't recommend placing adhesive on the fastener first. Place a dab of whichever adhesive you choose on the part of the model where the fastener is to be positioned.



Scale Motorsport
3 Topside Lane
Newtown, CT 06470-2023

Phone: 203.426.9686
Fax: 203.426.1397
email: scalemotor@aol.com
www.scalemotorsport.com

This product is not safe,
nor is it intended for use
by children under the age
of 12 years old.



Dzus Fasteners
Generally used to
fasten body panels.
Used generally on
cars built up to 1990.



Nut & Bolt End
To be used on the
opposite side of
Nut heads.



Phillips Head
General fastener.



Bolt Head
General fastener.



Washer
Used in combination
with Nut & Bolt Ends.



Dzus Fasteners
Generally used to
fasten body panels.
Used generally on
cars built up to 1990.



Nut & Bolt End
To be used on the
opposite side of
Nut heads.



Phillips Head
General fastener.



Bolt Head
General fastener.



Washer
Used in combination
with Nut & Bolt Ends.



Scale Motorsport
3 Topside Lane
Newtown, CT 06470-2023

Phone: 203.426.9686
Fax: 203.426.1397
email: scalemotor@aol.com
www.scalemotorsport.com

This product is not safe,
nor is it intended for use
by children under the age
of 12 years old.



Dzus Fasteners
Generally used to
fasten body panels.
Used generally on
cars built up to 1990.



Nut & Bolt End
To be used on the
opposite side of
Nut heads.



Phillips Head
General fastener.



Bolt Head
General fastener.



Washer
Used in combination
with Nut & Bolt Ends.



Dzus Fasteners
Generally used to
fasten body panels.
Used generally on
cars built up to 1990.



Nut & Bolt End
To be used on the
opposite side of
Nut heads.



Phillips Head
General fastener.



Bolt Head
General fastener.



Washer
Used in combination
with Nut & Bolt Ends.